



*Always be here with you!*



CE

# EXCAVATOR WE25



# Specifications

## Engine

Model	<b>Laidong 3TE30 22.1kW/2200rpm</b>
Type	<b>Electronic injection, water cooled, natural intake</b>
No. of cylinder	<b>3</b>

## Main Performance

Swing Speed (r/min)	<b>12-14</b>
Traveling Speed (km/H)	<b>2.8</b>
Grade ability (%)	<b>70(35°)</b>
Traveling Tracking Force (kN)	<b>15</b>
Bucket Digging Force (kN)	<b>11.5</b>
Arm Digging Force (kN)	<b>9.3</b>

## Hydraulic System

Hydraulic system working pressure (Mpa)	<b>16</b>
Hydraulic Pump (Gear Pump)	<b>AHWY</b>
Hydraulic pump flow (L/min)	<b>2×12+5</b>
Swing Motor	<b>Eaton</b>
Traveling Motor	<b>Eaton</b>
Fuel Tank Capacity (L)	<b>26</b>
Hydraulic Tank Capacity (L)	<b>27</b>

## Overall Dimensions

Overall Length (mm)	<b>4080</b>
Overall Width (mm)	<b>1300</b>
Overall Height (mm)	<b>2280</b>
Ground clearance (mm)	<b>490</b>
Track length (mm)	<b>1630</b>
Track width (mm)	<b>250</b>
Undercarriage width (mm)	<b>1270</b>
Undercarriage ground clearance (mm)	<b>235</b>
Dozer Blade (mm)	<b>1270×240</b>

## Operation parameters

Operation Weight (KG)	<b>2500</b>
Bucket Capacity (m <sup>3</sup> )	<b>0.1</b>
Max. Digging Radius (mm)	<b>4370</b>
Max. Digging Depth (mm)	<b>2450</b>
Max. Digging Height (mm)	<b>2290</b>
Max. Dumping Height (mm)	<b>3700</b>
Max. Dozer Cutting (mm)	<b>310</b>
Max. Dozer Lifting (mm)	<b>240</b>
Boom Deflexion (Left/Right) (°)	<b>70/50</b>
Tail Swing Radius (mm)	<b>1180</b>
Front Min. Swing Radius (mm)	<b>2020</b>





QINGDAO ZONGJIN ENGINEERING MACHINERY CO.,LTD.  
WOLF (QINGDAO) EQUIPMENT CO.,LTD.



Tel: 0086-532-66739792

Email: [info@chinawheelloaders.com](mailto:info@chinawheelloaders.com)

WeChat/Whatsapp: +8613589171650

Address: No.88 Chunyang Rd,Chengyang,Qingdao,China